A B C D E"

Specifcation of products

A B F G H I J K L M

A B l m H MFC !A-Y01

6 7 8 9 : ; < = > ? @

#$%&'()*"+$',¦)*"+%-'./)01.2/3"./45,204

N O P 6 7 Q " R S T " U V W
c d P Z ![\]^_! b[\ "_ [!\]
X Y P Z ![\]^_]!
` a P "_b_!!!
%|s}vwHrstruvwvxy! ~ _4z{s
$nnoppqqq4rstruvwvxy4z{s

e f	i j	j k
£ ¤ ¢	¡ ¢	g h

¥ ¦ m P ![""§ ¨ © ª P b!b_4]

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T_j (℃)	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$ $I_{F(AV)}$	Mean on-state current	180° half sine wave 50Hz Single side cooled, T_C=85°C	125			160	A
$I_{T(RMS)}$	RMS on-state current	Single side cooled, T_C=85°C	125			251	A
V_{DRM} V_{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	V_{DRM}&V_{RRM} tp=10ms V_{DSM}&V_{RSM}= V_{DRM}&V_{RRM}+200V respectively	125	600		2200	V
I_{DRM} I_{RRM}	Repetitive peak current	at V_{DRM} at V_{RRM}	125			20	mA
I_{TSM}	Surge on-state current	10ms half sine wave V_R=60%V_{RRM}	125			5.40	KA
I^2t	I^2T for fusing coordination					149	A^2s*10^3

OUTLINE DRAWING & CIRCUIT DIAGRAM

Rating and Characteristic




Fig. 1

Fig. 2


Fig. 3

Fig. 4

Fig. 5

Fig. 6

Rating and Characteristic


24
23
23
13
14
2−ø6.3
3−M6